Single Ended - G5.3

SPECIFICATIONS

LAMP DESCRIPTION
ORDERING CODE

CROSS REFERENCE

MANUFACTURER - LAMP #
EQUIPMENT MODEL #

EYH/FKT JCD120V-250WB
1000453

Watts	250W
Volts	120V
Color Temp	3050K
Approx Lumens	6050Lm
Average Life	150Hrs
Filament	CC-6
Burn Position	BD/Hor
Base	G5.3



MOL (A)	63.5mm
Lighted Length (B)	36.5mm
Bulb Diameter (C)	22mm

NUARC - VE-980

FBG/FBD JCD120V-500WCP
1000476

Watts	500W
Volts	120V
Color Temp	3200K
Approx Lumens	13200Lm
Average Life	50Hrs
Filament	CC-6
Burn Position	BD/Hor
Base	G5.3



MOL (A)	76mm
Lighted Length (B)	44.5mm
Bulb Diameter (C)	22mm

ITEK - 192511-001
435 (bottom)

DYH JCD120V-600WCP
1000246

Watts	600W
Volts	120V
Color Temp	3200K
Approx Lumens	17000Lm
Average Life	75Hrs
Filament	CC-6
Burn Position	BD/Hor
Base	G5.3



MOL (A)	63.5mm
Lighted Length (B)	36.5mm
Bulb Diameter (C)	22mm

ITEK - 192531-001
430 (top)

SMITH VICTOR
SV-403-004
SV-591; SV-592

DVY JCD120V-650WSP
1000225

Watts	650W
Volts	120V
Color Temp	3400K
Approx Lumens	20000Lm
Average Life	25Hrs
Filament	CC-6
Burn Position	BD/Hor
Base	G5.3





MOL (A)	63.5mm
Lighted Length (B)	36.5mm
Bulb Diameter (C)	22mm

ITEK - 198005-001
560

VISUAL GRAPHICS
62-12205-005

DYJ JCD230V-650WSP
1000247

Watts	650W
Volts	230V
Color Temp	3400K
Approx Lumens	20000Lm
Average Life	20Hrs
Filament	2CC-8
Burn Position	BD/Hor
Base	G5.3



MOL (A)	63.5mm
Lighted Length (B)	42.9mm
Bulb Diameter (C)	24mm

Single Ended - G6.35
GX6.35; GY6.35

SPECIFICATIONS

LAMP DESCRIPTION
ORDERING CODE

CROSS REFERENCE

MANUFACTURER - LAMP #
EQUIPMENT MODEL #

BRL JC12V-50W
1000071

Watts	50W
Volts	12V
Color Temp	3300K
Approx Lumens	1400Lm
Average Life	50Hrs
Filament	CBar6
Burn Position	BD/Hor
Base	G6.35



MOL (A)	44mm
Lighted Length (B)	30mm
Bulb Diameter (C)	11.5mm

DR. HELL
Scanner
SIEMENS

FDV JC24V-150W
1000505

Watts	150W
Volts	24V
Color Temp	3350K
Approx Lumens	4600Lm
Average Life	100Hrs
Filament	CBar6
Burn Position	BD/Hor
Base	G6.35



MOL (A)	50.8mm Lighted
Length (B)	30mm
Bulb Diameter (C)	14mm

SIMON OMEGA
471-027
VISUAL GRAPHICS
62-12205-003

EHJ JC24V-250W
1000290

Watts	250W
Volts	24V
Color Temp	3400K
Approx Lumens	8500Lm
Average Life	50Hrs
Filament	CBar6
Burn Position	BD/Hor
Base	G6.35



MOL (A)	55mm
Lighted Length (B)	33mm
Bulb Diameter (C)	13.5mm

JCV120V-1000WC4
1001822

Watts	1000W
Volts	120V
Color Temp	3200K
Approx Lumens	27000Lm
Average Life	100Hrs
Filament	2CC-8
Burn Position	BD/Hor
Base	GX6.35



MOL (A)	67.5mm
Lighted Length (B)	38mm
Bulb Diameter (C)	23mm

OLEC - L1KS
AL1KT; AL11KT;
ALKT

EVA JC12V-100H20
1000381

Watts	100W
Volts	12V
Color Temp	3000K
Approx Lumens	2000Lm
Average Life	2000Hrs
Filament	CBar6
Burn Position	BD/Hor
Base	GY6.35



MOL (A)	44mm
Lighted Length (B)	30mm
Bulb Diameter (C)	11.5mm

OLEC - L1CP
AL1CP; AL1CX

Single Ended - G9.5; GY9.5

SPECIFICATIONS

LAMP DESCRIPTION
ORDERING CODE

CROSS REFERENCE

MANUFACTURER - LAMP #
EQUIPMENT MODEL #

FEL JCV120V-1000WCH
1000509

Watts	1000W
Volts	120V
Color Temp	3200K
Average Life	375Hrs
Approx Lumens	27500Lm
Filament	CC-8
Burn Position	Any
Base	G9.5



MOL (A)	104mm
Lighted Length (B)	60.3mm
Bulb Diameter (C)	19mm

SCREEN USA (DS AMERICA)
Camera
NUARC

JCD120V-300WC
1000896

Watts	300W
Volts	120V
Color Temp	3200K
Average Life	100Hrs
Approx Lumens	7500Lm
Filament	CC-6
Burn Position	BD/Hor
Base	GY9.5



MOL (A)	63.5mm Lighted
Length (B)	36.5mm
Bulb Diameter (C)	22mm

BENCHER

DYS JCD120V-600WC
1000251

Watts	600W
Volts	120V
Color Temp	3200K
Average Life	75Hrs
Approx Lumens	17000Lm
Filament	CC-6
Burn Position	BD/Hor
Base	GY9.5



MOL (A)	63.5mm
Lighted Length (B)	36.5mm
Bulb Diameter (C)	22mm

DYR/220V JCD220V-650WC1
1000249

Watts	650W
Volts	220V
Color Temp	3200K
Average Life	50Hrs
Approx Lumens	16500Lm
Filament	2CC-8
Burn Position	BD/Hor
Base	GY9.5



MOL (A)	63.5mm
Lighted Length (B)	36.5mm
Bulb Diameter (C)	24mm

ITEK - 197632-001
560

DYR/240V JCD240V-650WC2
1000250

Watts	650W
Volts	240V
Color Temp	3200K
Average Life	50Hrs
Approx Lumens	16500Lm
Filament	2CC-8
Burn Position	BD/Hor
Base	GY9.5



MOL (A)	63.5mm
Lighted Length (B)	36.5mm
Bulb Diameter (C)	24mm

ITEK - 197632-001
560

Single Ended - G17t-7
BA15d, BA15s; E11

SPECIFICATIONS

LAMP DESCRIPTION
ORDERING CODE

CROSS REFERENCE

MANUFACTURER - LAMP #
EQUIPMENT MODEL #

BCK INC120V-500W
1000047

Watts	500W
Volts	120V
Color Temp	3250K
Average Life	50Hrs
Filament	C-13D
Burn Position	BD/Hor
Base	G17t-7



Bulb Diameter (A)	19.5mm
MOL (B)	88.9mm
Lighted Length (C)	39.7mm

VISUAL GRAPHICS
62-12205-002

ETB JCV120V-250WGBF
1000372

Watts	250W
Volts	120V
Color Temp	3000K
Average Life	2000Hrs
Approx Lumens	4800Lm
Filament	CC-8
Bulb Finish	Frosted
Burn Position	Any
Base	BA15d



Bulb Diameter (A)	13mm
MOL (B)	76mm
Lighted Length (C)	41mm

KENRO - 532-0025
2600

SM-100T8/1SC
8000044

Watts	100W
Volts	20V
Color Temp	3300K
Average Life	50Hrs
Approx Lumens	3050Lm
Filament	CC-6
Bulb Finish	Clear
Burn Position	Any
Base	BA15s



Bulb Diameter (A)	25mm
MOL (B)	76.2mm Lighted
Length (C)	55.6mm

NUARC - VE66

JCV100V-200WGS
1001800

Watts	200W
Volts	100V
Color Temp	2900K
Average Life	2000Hrs
Approx Lumens	2900Lm
Filament	CC-8
Burn Position	Any
Base	E11



Bulb Diameter (A)	14mm
MOL (B)	69mm
Lighted Length (C)	32.1mm

MITSUBISHI
CP-100 Platemaker